

PRODUCT NEWS

HULTAFORS GROUP 2012-11-01

RECOILLESS POWER, WITHOUT SPARKS

With the new dead blow hammer DB from Hultafors you can count on all the power you need, but with reduced recoil and without sparks. The dead blow function uses steel bearings to cushion the shock and reduce recoil. The design features soft faces that minimises the risk of leaving marks on the work piece, and a flat area on the head that allows upright storage. Ergonomic handle of fibreglass and a grip in Santoprene rubber.



DEAD BLOW HAMMER DB

Hammer head covered with Urethane and a dead blow function using steel bearings to cushion the shock and reduce recoil. Soft faces that is gentle on the work piece and non-sparking. Ergonomic handle of fibreglass and with a grip of Santoprene rubber.

- Soft faces, easy on the work piece.
- Dead blow function uses steel bearings to cushion the shock and reduce recoil.
- Ergonomic handle of fibreglass and grip of Santoprene rubber.
- Non-sparking
- Flat area on head allows upright storage

PRODUCT INFORMATION

BEST NR.	NAME	MODEL	WEIGHT	SHAFT LENGTH	SHAFT	L	В	Н	Ø	QTY/PACK	BAR CODE
823411	DEAD BLOW HAMMER	DB 600	570 g	240 mm	G	295	96	50	43	2	7391408234115
823412	DEAD BLOW HAMMER	DB 1200	1160 g	282 mm	G	353	128	64	50	2	7391408234122
823413	DEAD BLOW HAMMER	DB 1600	1600 g	342 mm	G	424	150	74	60	1	7391408234139
823414	DEAD BLOW HAMMER	DB 5000	5700 g	838 mm	G	975	232	104	88	1	7391408234146